



**RIDEWELL
SUSPENSIONS**

RUL-245 "Bantamweight" Series Auxiliary Liftable Air-Rides for Truck and Trailer Applications



Mod. RUL-245
for I-Beam Axles with
Permanently Locked Tie Rods.
Double or triple-convoluted
air springs. 13,000 lb. cap.
(Truck applications only)



Advantages to Improve Your Bottom Line!

- ✓ LOW COST
- ✓ EASY INSTALLATION
- ✓ MAINTENANCE FREE
- ✓ WEIGHT SAVINGS UP TO 650+ LBS.
OVER COMPARABLE 20,000 LB. UNITS
- ✓ ULTRA-COMPACT DESIGN FITS SHORT
WHEEL BASES
- ✓ HIGH AXLE TRAVEL
- ✓ CORRESPONDING AIR CONTROL KITS

Eccentric bolt now standard in left and right hanger for simple, manual axle alignment

- Options:
- ✓ Unitized with axles
 - ✓ Custom applications

Mod. RUL-245
for 5" Round Axles,
Straight or Drop.
13,000 lb. cap.



Ridewell's RUL-245 "Bantamweight" Suspensions

Covered Under U.S. and Foreign Patents, Existing and Applied For.

Applications - all with eccentric bolts	AXLE TYPE	SUSPENSION PART NUMBER	MOUNTING HEIGHT LOADED	AXLE TRAVEL					
				"UP"	"DOWN"	"TOTAL"			
	Truck Tag or Pusher I-Beam Axle, 3 1/2" Drop with Permanently Locked Tie Rod	2450004 Double-Convoluted Air Springs	7"	4 1/2"	4 3/8"	8 7/8"			
			8"	5 1/2"	3 3/8"	8 7/8"			
		2450005 Triple-Convoluted Air Springs	9"	5 9/16"	5 3/16"	10 3/4"			
			10"	6 9/16"	4 3/16"	10 3/4"			
			11"	7 9/16"	3 3/16"	10 3/4"			
			12"	8 9/16"	2 3/16"	10 3/4"			
	Truck Tag or Pusher Round 5" Axle, Straight or Drop-Center	24510700 Triple-Convoluted Air Springs	13 3/4"	7"	3 3/4"	10 3/4"			
			14 1/2"	7 3/4"	3"	10 3/4"			
			15 1/4"	8 1/2"	2 1/4"	10 3/4"			
		2450020 Triple-Convoluted Air Springs	13 3/4"	6 3/8"	4 11/16"	11 1/16"			
			14 1/2"	7 1/8"	3 15/16"	11 1/16"			
			15 1/4"	7 7/8"	3 3/16"	11 1/16"			
		2450021 Triple-Convoluted Air Springs	11"	4 3/8"	4 5/8"	9"			
			11 1/2"	4 7/8"	4 1/8"	9"			
			12"	5 3/8"	3 5/8"	9"			
			12 1/2"	5 7/8"	3 1/8"	9"			
				Trailer 5" Round Axle	2450008 Triple-Convoluted Air Springs	13 3/4"	6 3/8"	4 11/16"	11 1/16"
						14 1/2"	7 1/8"	3 15/16"	11 1/16"
15 1/4"	7 7/8"	3 3/16"				11 1/16"			
2450009	15"	4 7/8"			6 5/8"	11 1/2"			
	16"	5 7/8"			5 5/8"	11 1/2"			
	17"	6 7/8"			4 5/8"	11 1/2"			
2450010	17"	6 1/2"	6 1/4"	12 3/4"					
	18"	7 1/2"	5 1/4"	12 3/4"					
	19"	8 1/2"	4 1/4"	12 3/4"					
	2450011	19"	6 1/2"	6 1/4"	12 3/4"				
		20"	7 1/2"	5 1/4"	12 3/4"				
2450011	21"	8 1/2"	4 1/4"	12 3/4"					
	22"	9 1/2"	3 1/4"	12 3/4"					

RIDEWELL SUSPENSIONS P.O. Box 4586 Springfield, MO 65808 Ph: (417) 833-4565 Fax: (417) 833-4560
www.ridewellcorp.com

Ridewell Corporation • P.O. Box 4586 • Springfield, MO 65808-4586
800-641-4122 • (417) 833-4565 • Fax: (417) 833-4560 • www.ridewellcorp.com