

Drum Brake Axle for Trailer - Order Guide

Complete form below and email to: Info@ridewellcorp.com
Form can be faxed to: **Customer Service - (417) 833-4560**

Contact:	Email/Phone:
----------	--------------

Note:	
-------	--

Requires Generic Parking Brake CMVSS-121 (TSD-121 S5.6.1) – *Approval by Ridewell Engineering Department required.*

Suspension Type	<input type="checkbox"/> Air-Ride	<input type="checkbox"/> Mechanical (Spring)
------------------------	-----------------------------------	--

Axle-Track Width	<input type="checkbox"/> 71.5"	<input type="checkbox"/> 77.5"	<input type="checkbox"/> Other _____
-------------------------	--------------------------------	--------------------------------	--------------------------------------

12.25" x 7.5" – DRUM BRAKE SIZE

Spindle Type	<input type="checkbox"/> (N) Tapered – Straight-Axle Only
---------------------	---

Axle Diam/Wall Thickness	<input type="checkbox"/> 5" x 0.59"	<input type="checkbox"/> 5" x 0.75"
---------------------------------	-------------------------------------	-------------------------------------

Brake Capacity	<input type="checkbox"/> 20K
-----------------------	------------------------------

Automatic Slack Adjuster	<input type="checkbox"/> RW Standard	<input type="checkbox"/> Haldex®	<input type="checkbox"/> No Slack Adjuster
---------------------------------	--------------------------------------	----------------------------------	--

Brake Chamber	<input type="checkbox"/> Spring Brake	<input type="checkbox"/> Service Brake Only	<input type="checkbox"/> No Chamber
----------------------	---------------------------------------	---	-------------------------------------

Hub (Hub-Piloted–8-Stud x 10.83" Bolt Circle)	Drum Option	<input type="checkbox"/> RW Standard	<input type="checkbox"/> No Drum
--	--------------------	--------------------------------------	----------------------------------

16.5" x 7.0" – DRUM BRAKE SIZE

Spindle Type	<input type="checkbox"/> (P) Parallel	<input type="checkbox"/> (N) Tapered
---------------------	---------------------------------------	--------------------------------------

Beam Style	<input type="checkbox"/> Straight-Axle	<input type="checkbox"/> 6.25" Drop-Axle	<input type="checkbox"/> 6.25" Inverted Drop-Axle	<input type="checkbox"/> 8" Drop-Axle
-------------------	--	--	---	---------------------------------------

Axle Diam/Wall Thickness	<input type="checkbox"/> 5" x 0.47" <small>Mechanical (Spring) SUSP</small>	<input type="checkbox"/> 5" x 0.59"	<input type="checkbox"/> 5" x 0.75"	Straight-Axle Only <input type="checkbox"/> 5.75" x 0.335" <input type="checkbox"/> 5.75" x 0.394"
---------------------------------	--	-------------------------------------	-------------------------------------	---

Brake Capacity (Extra-Life)	<input type="checkbox"/> 20K	<input type="checkbox"/> 23K
------------------------------------	------------------------------	------------------------------

Automatic Slack Adjuster	<input type="checkbox"/> RW Standard	<input type="checkbox"/> Haldex®	<input type="checkbox"/> Bendix®	<input type="checkbox"/> Gunite®	<input type="checkbox"/> No Slack Adjuster
---------------------------------	--------------------------------------	----------------------------------	----------------------------------	----------------------------------	--

Brake Chamber	<input type="checkbox"/> Spring Brake	<input type="checkbox"/> Service Brake Only	<input type="checkbox"/> No Chamber
----------------------	---------------------------------------	---	-------------------------------------

Hub (Hub-Piloted–10-Stud x 11.25" Bolt Circle)	Hub-Lightweight Option	<input type="checkbox"/> WEMC® (ADI)	<input type="checkbox"/> ConMet® (ALUM)	<input type="checkbox"/> ConMet PreSet® Plus (ALUM)
---	-------------------------------	--------------------------------------	---	---

Drum Option	<input type="checkbox"/> RW Standard	<input type="checkbox"/> Lightweight	<input type="checkbox"/> No Drum
--------------------	--------------------------------------	--------------------------------------	----------------------------------

OPTIONS

Wheel Data	Long Stud	Short Stud
-------------------	-----------	------------

	<input type="checkbox"/> Dual Alum Wheel	<input type="checkbox"/> Dual Steel Wheel	<input type="checkbox"/> Single Alum Wheel	<input type="checkbox"/> Single Steel Wheel
--	--	---	--	---

Hub Seal	<input type="checkbox"/> Stemco Guardian® HP	<input type="checkbox"/> National Gold PTFE
-----------------	--	---

Hub Lubrication	<input type="checkbox"/> 80/90 Gear Oil (Std)	<input type="checkbox"/> SYN Oil (75W-90)	<input type="checkbox"/> SYN Semi-Fluid Grease	<input type="checkbox"/> SYN Grease (Hard)	<input type="checkbox"/> No Lube (Ship Dry)
------------------------	---	---	--	--	---

Cambered	<input type="checkbox"/> Yes
-----------------	------------------------------

Dust shield	<input type="checkbox"/> Yes
--------------------	------------------------------

Cam Enclosure	<input type="checkbox"/> Yes (Not available on all axles-Contact Ridewell)
----------------------	--

ABS	<input type="checkbox"/> Tone Ring Only	<input type="checkbox"/> Tone Ring and Sensor
------------	---	---

AUTOMATIC TIRE INFLATION SYSTEM (ATIS) – *Select axle preparation procedure and provide required information.*

	<input type="checkbox"/> No ATIS
--	----------------------------------

Axle Preparation	<input type="checkbox"/> Basic 1-Hole	<input type="checkbox"/> Basic 3-Hole	<input type="checkbox"/> P.S.I. ThermALERT™
-------------------------	---------------------------------------	---------------------------------------	---

Wheel Size	<input type="checkbox"/> 17.5"	<input type="checkbox"/> 19.5"-to-24.5"
-------------------	--------------------------------	---

Number of Axles	<input type="checkbox"/> Single Axle	<input type="checkbox"/> Tandem Axle	<input type="checkbox"/> Tri-Axle
------------------------	--------------------------------------	--------------------------------------	-----------------------------------