




Axle Order Form Disc Brakes



*= required field

CONTACT INFORMATION

*Company Name _____ *Contact Name _____
Address _____ Email _____
City _____ Office # _____
State _____ Mobile # _____
Zip Code _____

TRAILER INFORMATION

Trailer Type (Choose one) _____ Number of Axles _____
(tank, flatbed, livestock, dump, etc.) Axle Spacing _____

*Axle Track	☐ 71.5"	Trailer Usage	☐ On-Road
	☐ 77.5"		☐ Off-Road
	☐ Other (Please specify) _____		☐ Mixed _____ % Off-Road
Suspension Type	☐ Air-Ride	*Wheel Data	☐ Single-Wheel
	☐ Mechanical (Leaf Spring)		☐ Dual-Wheel
Suspension Capacity	☐ 23K	*Wheel Size	☐ 17.5"
	☐ 25K		☐ 19.5"- 24.5"

AXLE SPECIFICATIONS

Axle Diameter	☐ 5" Round	Axle Capacity	☐ 23K (.59" Wall Thickness)
Spindle Type	☐ Parallel ("P" Spindle)		☐ 25K (.75" Wall Thickness)
Axle Beam Style	☐ Straight-Axle	Cambered	☐ Yes
			☐ No

BRAKE SPECIFICATIONS

Brake Size	☐ Bendix ADB22X-LT®	Chambers	☐ Parking Brake (18/24)
	☐ Haldex DBT22LT®		☐ Service Brake Only (Type 18)
	☐ Wabco PAN™ 19		☐ No Brake Chambers
	☐ Wabco PAN™ 17		☐ Other (Please specify) _____
	☐ No Brakes		
Brake Capacity	☐ 20K		
	☐ 23K		

NOTE: Wabco PAN 19 offered on 25k Axles and Wabco PAN 17 offered on 23k Axles

NOTE: For Canadian Application it requires generic parking brake CMVSS-121 (TSD-121 S5.6.1). Engineering Dept approval required.

WHEEL-END SPECIFICATIONS

Hub Type	☐ Cast Iron ☐ Aluminum ☐ ADI ☐ No Hub	Stud Length	☐ Long ☐ Short (Special Order)
Bolt Pattern	☐ 10 Stud x 11.25" Bolt Circle ☐ 8 Stud x 10.83" Bolt Circle (For PAN 17 Brakes)		
Lubrication	☐ Oil, 80/90 ☐ Synthetic Oil (75W-90) ☐ Synthetic Semi-Fluid Grease ☐ Dry or No Lubrication (Comes with Oil Hubcap)		

NOTE: Hubs come standard with Side Fill and Tone Rings

OPTIONS

ABS Sensor	☐ Yes ☐ No	Dust Shields	☐ Yes ☐ No
Cam Covers	☐ Yes (Not available on all axles, contact Ridewell) ☐ No		

TIRE INFLATION

Tire Inflation Prep	☐ Basic 1-Hole Prep ☐ Basic 3-Hole Prep ☐ PSI Tire Inflation System
---------------------	---