




Axle Order Form Disc Brakes



*= required field

CONTACT INFORMATION

*Company Name _____ *Contact Name _____
Address _____ Email _____
City _____ Office # _____
State _____ Mobile # _____
Zip Code _____

TRAILER INFORMATION

Trailer Type (Choose one) _____ Number of Axles _____
(tank, flatbed, livestock, dump, etc.) Axle Spacing _____

*Axle Track ☐ 71.5" ☐ 77.5" ☐ Other (Please specify) _____
Trailer Usage ☐ On-Road ☐ Off-Road ☐ Mixed _____ % Off-Road
Suspension Type ☐ Air-Ride ☐ Mechanical (Leaf Spring) *Wheel Data ☐ Single-Wheel ☐ Dual-Wheel
Suspension Capacity ☐ 23K ☐ 25K Wheel Size ☐ 19.5"- 24.5"

AXLE SPECIFICATIONS

Axle Diameter ☐ 5" Round Axle Capacity ☐ 23K (.59" Wall Thickness) ☐ 25K (.75" Wall Thickness)
Spindle Type ☐ Parallel ("P" Spindle) Cambered ☐ Yes ☐ No
Axle Beam Style ☐ Straight-Axle

BRAKE SPECIFICATIONS

Brake Size ☐ Bendix ADB22X-LT® ☐ Haldex DBT22LT® ☐ Wabco PAN™ 19 ☐ No Brakes
Chambers ☐ Parking Brake (18/24) ☐ Service Brake Only (Type 18) ☐ No Brake Chambers ☐ Other (Please specify) _____
Brake Capacity ☐ 20K ☐ 23K

NOTE: Wabco PAN 19 offered on 25k Axles

NOTE: For Canadian Application it requires generic parking brake CMVSS-121 (TSD-121 S5.6.1). Engineering Dept approval required.

WHEEL-END SPECIFICATIONS

Hub Type	☐ Cast Iron ☐ Aluminum ☐ ADI ☐ No Hub	Stud Length	☐ Long ☐ Short (Special Order)
Bolt Pattern	☐ 10 Stud x 11.25" Bolt Circle		
Lubrication	☐ Oil, 80/90 ☐ Synthetic Oil (75W-90) ☐ Synthetic Semi-Fluid Grease ☐ Dry or No Lubrication (Comes with Oil Hubcap)		

NOTE: Hubs come standard with Side Fill and Tone Rings

OPTIONS

ABS Sensor	☐ Yes ☐ No	Dust Shields	☐ Yes ☐ No
Cam Covers	☐ Yes ☐ No		

TIRE INFLATION

Tire Inflation Prep	☐ Basic 1-Hole Prep ☐ Basic 3-Hole Prep ☐ PSI Tire Inflation System
---------------------	---